

# PCAN-USB FD (IPEH-004022)

---



## 1. Product Overview

The PCAN-USB FD by PEAK-System is a compact USB interface that enables a computer to connect to CAN and CAN FD networks. With high-speed USB 2.0 connectivity, full support for CAN 2.0A/B and CAN FD standards, and galvanic isolation up to 500 V, this adapter is well-suited for mobile, desktop, and embedded development environments. Its simple plug-and-play operation and included monitoring and programming software make it a complete solution for CAN-based diagnostics and development.

## 2. Key Features

- High-speed USB 2.0 interface (compatible with USB 1.1 and USB 3.0)
- Supports CAN 2.0A/B and CAN FD protocols
- CAN FD data rates from 25 kbit/s to 12 Mbit/s, up to 64-byte payloads
- Classical CAN bit rates from 25 kbit/s to 1 Mbit/s
- Time stamp resolution of 1  $\mu$ s
- Galvanic isolation up to 500 V between PC and CAN network
- D-Sub 9-pin CAN connection (CiA® 106 compliant)
- CAN transceiver: NXP TJA1044GT
- FPGA implementation of the CAN FD controller
- CAN termination via solder jumper
- Optional +5 V supply to CAN via jumper (e.g., for external converters)

- Error injection and overload frame support
- Bus load measurement including error and overload frames
- Powered via USB, no external supply required
- Operating temperature: -40 °C to +85 °C
- Compact and rugged plastic housing

### 3. Technical Specifications

- CAN Bit Rate: 25 kbit/s to 1 Mbit/s
- CAN FD Bit Rate: 25 kbit/s to 12 Mbit/s (data field, up to 64 bytes)
- Time Stamp Resolution: 1 µs
- CAN Standard: ISO 11898-2, CAN 2.0A/B, CAN FD (ISO/Non-ISO)
- CAN Controller: FPGA-based implementation
- CAN Transceiver: NXP TJA1044GT
- Galvanic Isolation: Up to 500 V
- Operating Temperature: -40 °C to +85 °C
- Power Supply: Via USB
- Connector: D-Sub, 9-pin (CiA® 106)

### 4. D-Sub 9 Connector Pinout

Pin	Function
1	Not connected / optional +5V
2	CAN-L
3	GND
4	Not connected
5	Not connected
6	GND
7	CAN-H
8	Not connected
9	Not connected

•